

**A reliable hood for clean kitchen air**

The 300 ExtractionTech Standard cooker hood efficiently removes cooking odours from your kitchen with its reliable motor. Enjoy a consistently fresh and pleasant environment every time you cook.

Product Benefits & Features**ExtractionTech Standard. Reliable odour extraction**

The ExtractionTech Standard hood features a reliable motor for effective odour extraction while preparing meals. Your kitchen environment remains fresh and clean for a better cooking experience, everyday.

**Light up your cooking with Pure Illumination**

Our Pure Illumination provides intense lighting for full visibility while cooking. The LED lights illuminate your entire cooking surface, making it easy to see every detail of your meal preparation.

**Grease filter with reliable performance**

Experience reliable grease filtering. Designed for convenience, it can be easily cleaned by hand or in the dishwasher, ensuring your kitchen stays fresh and your hood performs at its best.

- Installation type: Pull-out, width 60 cm
- Air extraction capacity (high/low): 440 / 170 m³/h
- Noise min/max/intensive: 41/60/dB(A)
- Number of speeds: 3; Micro switch
- Cooker hood lamps type and number: LED stripe, 1
- Push button controls with 3; Micro switch speeds
- Return flap
- Grease filter type and number: Aluminium mesh, 2
- Air extraction or recirculation possible, if charcoal filter (optional accessory) installed.
- LongLife charcoal filter can be bought as accessory
- Recirculation capacity, man/max/intensive: 140/345/ m³/h

Product Specification

Main colour	Grey	Product Number Code	942 022 624
Speeds	3; Micro switch	Bar code	7332543810277
Control type	Mechanical push buttons	Net weight, kg	10.5
Lamp type	LED stripe	Gross weight, kg	12.3
Energy efficiency class Hood	C	Dimensions HxWxD in mm	395x598x300
Hoods_Capacity_Min_Max_Intensive_m3h	170/440/-	Installation	Pull-out
Hoods_Noiselevel_Min_Max_Intensive_dB	41/60/-	Grease filter, n° of	2
Grease filter efficiency class	C	Central_Techspeg_Hoods_GreaseFilterType	Aluminium mesh
Min dist.from cook.top electric, cm	45	Cord length, m	1.4
Min dist.from cook.top gas, cm	65	Air outlet, mm	150
Annual Energy consumption, KWh/annum	57.6	OdourClean Standard Carbon filter	Optional Accessory
Size, cm	60	OdourClean Standard Carbon filter type	MCFB82ST
Recirculatory	Yes	OdourClean Plus Carbon filter type	MCFB83PL
External evacuation	Yes	OdourClean Pro Carbon filter type	MCFB75PR
Light temperature, K	3000	OdourClean Plus Carbon filter	Optional Accessory
Lamp, n° of	1	OdourClean Pro Carbon filter	Optional accessory
Fluid dynamic efficiency class	C	Nordic_Series_and_Themes	300
Lighting efficiency class	A	Nordic_CH_Cap_MinMaxInt_SecGen	170/440/-
Recirculation Min, m³/h-2ndGen	140	Nordic_CH_Noise_MinMaxInt_SecGen	41/60/-
Recirculation Max, m³/h-2ndGen	345	Test_MotorType	Standard
Recirc. sound power min, dB(A)	49	Nordic_CH_ControlType	Push buttons
Recirc. sound power max, dB(A)	68	Nordic_CH_Lamps_TyNo	1, LED stripe
		Nordic_CH_MinDistanceElectricGas	45/65

