ECOFLOW

# DELTA 3 Classic

## GENERAL

**Color**
Light Gray

**Capacity**
1024wh

**Net Weight**
12.1kg±0.3kg

**Dimension**
398*200*283mm

**Total Output Ports**
5

## AC OUTPUT

**Max Output**
1800W
230V~50Hz

**Surge Output**
3600W

**Max Output by X-Boost**
2400w

**Output Voltage**
230v

**UPS**
10ms, UPS

**AC Outlets Number**
2

## DC OUTPUT

**USB-A-Fast**
1*12W

**USB-C**
1*100w
+1*30W

**12V DC Output**
None

## AC INPUT

**Utility Power Charging**
1400w

**Generator Charging**
1400w

**0-80% Charge Time**
**Fast Mode:** 45min

**0-100% Charge Time**
60min

**Input Voltage**
220-240V~50/60Hz

## DC INPUT

**Solar Charging**
500W Max
DC charge input*1
11V-60V 500W Max*1

**Alternator Charger**
PV-based XT60 Port, 500w Alternator Charger

## BATTERY

**Battery Chemistry**
LFP

**Cycle Life**
10 years

**IP Rate for Battery Pack**
IP20 for complete product

**CTC Craftsmanship**
Yes

**Extra Battery Port**
None

**Extra Battery**
None

**Max Capacity with Extra Battery**
None

## CONNECTION

**Screen**
Yes

**WiFi**
Yes

**Bluetooth**
Yes

**App**
Yes
(Storm, Bypass Unbind Mode)

## EXPERIENCE

**Years of Warranty**
3+2 years

**Noise**
600w <30dB
1200W <40dB
Maximum capacity 50dB

**Operating Altitude**
3000m

**Discharge Temperature**
–10°C to 45°C

**Storage Temperature**
–10°C to 45°C
(optimal: 20°C to 30°C)

**Charge Temperature**
0°C to 45°C

## BATTERY PROTECTION

Over Voltage Protection, Overload Protection, Over Temperature Protection, Short Circuit Protection, Low Temperature Protection, Low Voltage Protection, Overcurrent Protection

## WHAT IS IN THE BOX?

1. EcoFlow DELTA 3 Classic portable power station *1
2. AC charging cable *1
3. Manuals and warranty card